Program: BE Computer Engineering

Curriculum Scheme: Revised 2016

## Examination: Final Year Semester VII

## Course Code: CSC702 and Course Name: MCC

Time:	1	hour
-------	---	------

Max. Marks: 50

Note to the students:- All the Questions are compulsory and carry equal marks .

Q1.	The 2G GSM technology uses a carrier separation of
Option A:	1.25 MHz
Option B:	200 KHz
Option C:	30 KHz
Option D:	300 KHz
Q2.	In direct sequence process which step is performed first?
Option A:	De-spreading
Option B:	Demodulation
Option C:	Dispreading & Demodulation
Option D:	Desperation
Q3.	Fading of the received radio signals in a mobile communication environment
	occurs because of
Option A:	Direct propagation
Option B:	Multipath Propagation
Option C:	Bi-path Propagation
Option D:	Tri-path propagation
Q4.	In a GSM architecture, which system provides Authentication and Encryption
	services?
Option A:	HLR
Option B:	VLR
Option C:	EIR
Option D:	AUC
Q5.	A UMTS(Universal Mobile Telecommunication) network is a network.
Option A:	First Generation
Option B:	Second Generation
Option C:	Third Generation
Option D:	Fourth Generation

Q6.	What is the maximum data rate supported by a 3G network or UMTS network?		
	384 kbps		
Option A:	2 Mbps		
Option B:	32 Mbps		
Option C:			
Option D:	42 Mbps		
Q7.	As part of Closed Loop Power Control followed by a WCDMA network, power control bits are sent every milliseconds to the User Equipment (Phones).		
Option A:	0.1 ms		
Option B:	0.66 ms		
Option C:	1.5 ms		
Option D:	2.58 ms		
Q8.	Who developed standards for a UMTS network?		
Option A:	ANSI (American National Standards Institute)		
Option B:	3GPP (3rd Generation Partnership Project)		
Option C:	ITU (International Telecommunication Union)		
Option D:	IEEE		
Q9.	The DoD model (also called the TCP/IP stack) has four layers. Which layer of the		
	DoD model is equivalent to the Network layer of the OSI model?		
Option A:	Application		
Option B:	Host to Host		
Option C:	Internet		
Option D:	Network Access		
Q10.	A set that makes stationary or mobile wireless station and also have optional		
	central base station is known as		
Option A:	Basic service set		
Option B:	Extended service set		
Option C:	Network point set		
Option D:	Access point		
Q11.	Which of the following internet layer protocols of TCP/IP is used for wireless		
	communication?		
Option A:	Mobile IP		
Option B:	IP		
Option C:	ТСР		
Option D:	UDP		
0.10			
Q12.	What is the condition for handoff?		
Option A:	A mobile move into a different cell while in conversation		
Option B:	A mobile remains in the same cell while in conversation		
Option C:	A mobile move to different cell when idle		
Option D:	A mobile remains in the same cell and is idle		

Which of the following priority handoff method decrease the probability of forced		
termination of a call due to lack of available channels?		
Queuing		
Guard channel		
Cell dragging		
Near far effect		
Bluetooth uses		
frequency hopping spread spectrum		
orthogonal frequency division multiplexing		
time division multiplexing		
channel division multiplexing		
In a piconet, there can be up to parked nodes in the network.		
63		
127		
255		
511		
Bluetooth transceiver devices operate in band.		
2.4 GHz ISM		
2.5 GHz ISM		
2.6 GHz ISM		
2.7 GHz ISM		
Which of the following WLAN standard has been named Wi-Fi?		
IEEE 802.6		
IEEE 802.15.4		
DSSS IEEE 802.11b		
IEEE 802.11g		
Which of the following standard committee specifies Bluetooth and other		
Personal Area Networks (PAN)?		
IEEE 802.11b		
IEEE 802.15		
IEEE 802.11g		
IEEE 802.16		
Multi-Layer Mobility Management using Hybrid SIP provide mobility in		
following layer		
Network layer		
Data link layer		
Application layer		
Transport layer		

Q20.	Protocol is employed to line up the net phone, phone calls,
	video conferencing and alternative transmission connections.
Option A:	SIP
Option B:	VoIP
Option C:	IP
Option D:	Mobile IP.
Q21.	enables the serving networks to locate a mobile subscriber's point of attachment for delivering data packets.
Option A:	Location management
Option B:	Hand-off management
Option C:	Mobility Management
Option D:	Region Management
Q22.	LTE Mac layer responsible for
Option A:	re-segmentation of RLC data PDUs
Option B:	Mapping between logical channels and transport channels, Multiplexing of MAC SDUs
Option C:	Carries all information from the MAC transport channels over the air interface
Option D:	Mapping between MAC and PDU
Q23.	LTE Physical layer responsible for
Option A:	re-segmentation of RLC data PDUs
Option B:	Mapping between logical channels and transport channels, Multiplexing of MAC SDUs
Option C:	Carries all information from the MAC transport channels over the air interface
Option D:	Mapping between MAC and PDU
Q24.	strives towards the "plug-and-play" paradigm in the way that new base stations shall automatically be configured and integrated into the network.
Option A:	Self-configuration functions
Option B:	Self-optimization functions
Option C:	Self-healing functions
Option D:	Self-autocorrelation functions
Q25.	When some nodes in the network become inoperative,
<u> </u>	mechanisms aim at reducing the impacts from the failure
Option A:	Self-configuration functions
Option B:	Self-optimization functions
Option C:	Self-healing functions
Option D:	Self-autocorrelation functions